

HTC-24

TRACKED TRENCHER



POWERFUL
Reliable Performance



BUILT TOUGH
Made to Last



JOB READY
Every Time



DIMENSIONS & WEIGHT

Transport Length	2,450 mm
Transport Width	924 mm
Transport Height	1,200 mm
Operating Weight	700 kg
Overall Length (Pedal Unfolded)	2,615 mm



MACHINE OFFSET

Distance from trench centreline to outside of machine.

Left Side	525 mm
Right Side	399 mm



ENGINE

Engine Options	Runtong R740-1 / Honda GX690
Rated Power	22 HP
Rated Speed	3,600 rpm
Noise Level	≤ 95 dB



HYDRAULIC & DRIVE SYSTEM

Ground Drive	Hydraulic; infinitely variable from zero to maximum; speed and direction control
Digging Chain Drive	Direct hydraulic drive; single speed (forward and reverse)
Pump Drive	Directly driven by the engine
Hydraulic Pressure	0-18 MPa
Travel Speed	0-4.5 km/h
Auxiliary Flow Rate	0-42 L/min
Chain Speed	0-185 rpm
Trenching Speed	0-50 m/min



TRENCHING PERFORMANCE

Trenching Depth	750 mm
Trenching Width	152 mm



FLUIDS

Fuel Tank	15 L
Engine Oil	1.7 L
Hydraulic Tank	30 L



**BUILT FOR
TOUGH JOBS**
Engineered for Productivity



POWER



DURABILITY



PERFORMANCE



RELIABILITY